



RAL 9010



24 Volt
Safety Voltage



Versione DALI disponibile a richiesta
DALI version available on request



Vedere pagina 168 per i kit che includono il driver LED - See page 168 for kits including LED driver



Type	Part N°	Dimensions (mm)	Colour	°Kelvin	Lumen	Power (W)	Installation hole (mm)	Packing box dimensions (mm)	Weight (kg)
ROUND 95 NW	BD09524TNW1B	Ø 95x28h	Natural White	4200°K	395	7	Ø 80	200x150x60h	0,21
ROUND 95 WW	BD09524TWW1B	Ø 95x28h	Warm White	3000°K	372	7	Ø 80	200x150x60h	0,21
ROUND 140 NW	BD14024TNW1B	Ø 140x28h	Natural White	4200°K	695	10	Ø 120	240x180x60h	0,33
ROUND 140 WW	BD14024TWW1B	Ø 140x28h	Warm White	3000°K	656	10	Ø 120	240x180x60h	0,33
ROUND 170 NW	BD17024TNW1B	Ø 170x31h	Natural White	4200°K	1066	14	Ø 145	260x200x60h	0,43
ROUND 170 WW	BD17024TWW1B	Ø 170x31h	Warm White	3000°K	1006	14	Ø 145	260x200x60h	0,43
ROUND 200 NW	BD20024TNW1B	Ø 200x31h	Natural White	4200°K	1195	16	Ø 180	330x230x60h	0,57
ROUND 200 WW	BD20024TWW1B	Ø 200x31h	Warm White	3000°K	1127	16	Ø 180	330x230x60h	0,57
ROUND 275 NW	BD27524TNW1B	Ø 275x31h	Natural White	4200°K	2167	27	Ø 250	380x340x60h	1,00
ROUND 275 WW	BD27524TWW1B	Ø 275x31h	Warm White	3000°K	2044	27	Ø 250	380x340x60h	1,00
ROUND 330 NW	BD33024TNW1B	Ø 330x31h	Natural White	4200°K	2876	34	Ø 310	470x360x60h	1,70
ROUND 330 WW	BD33024TWW1B	Ø 330x31h	Warm White	3000°K	2713	34	Ø 310	470x360x60h	1,70

Incasso a LED tondo extrapiatto

- Cornice e struttura in alluminio verniciato
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore 24V DC specifico (fornito a richiesta)
- Consumo limitato
- Lunga durata

Round extra flat recessed LED fixture

- Structure and frame in lacquered aluminium
- Extra flat
- Safety low voltage with specific 24V DC drivers (supplied on request)
- Limited consumption

Runde extraflache LED Einbaustrahler

- Rahme und Körper aus lackiertem Aluminium
- NV-Betrieb durch besonderen 24VDC Transformator (auf Anfrage geliefert)
- Begrenzter Verbrauch
- Lange Lebensdauer

Encastrable à LED rond extra plat

- Encadrement et corps en aluminium verni
- Luminosité très homogène
- Il marche en basse tension avec un transformateur 24V DC (livré sur demande)
- Consommation limitée
- Longue durée de vie

Focos empotrables a LED extra plano

- Estructura y marco de aluminio pintado
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con drivers específicos de 24VDC (bajo demanda)
- Bajo consume
- Larga vida